



## Nika dp

### TECHNICAL DATA NIKA dp\*

HINGES:	180° 4-dimensional adjustable (both left and right)
LOCK:	LOCINOX lock with stainless steel plus eurocylinder with 3 keys included
ANCHORING KEEP:	LOCINOX type SECURA
DROP BOLT:	LOCINOX Suby integrated drop bolt
LEAFHEIGHT (WINGHEIGHT):	Minus 50 mm between the ground surface and the leaf
FENCE CONNECTION:	Optional for wire mesh or steel cage fence
AVAILABLE FINISHES:	Hot dip galvanised according ISO EN 1461 Hot dip galvanised according ISO EN 1461 + powderpainted in any available RAL colour according NEN 5254.

Above: detail 180° hinge  
Middle: SECURA keep  
Under: Suby drop bolt

### ZINC & POWDER PAINT

Available heights: 800 mm | 1000 mm | 1250 mm | 1500 mm | 1800 mm | 2000 mm | 2500 mm

Width gate:	Post section	Vert. pipe (lock)	Vert. pipe (hinge)	Upper crossbar	Lower crossbar
2000 mm	100x100x3	50x50x2	50x50x2	50x50x2	50x50x2
2500 mm	100x100x3	50x50x2	50x50x2	50x50x2	50x50x2
3000 mm	100x100x3	50x50x2	50x50x2	50x50x2	50x50x2
3500 mm	100x100x3	50x50x2	50x50x2	50x50x2	50x50x2
4000 mm	100x100x3	50x50x2	50x50x2	50x50x2	50x50x2
4500 mm	100x100x3	50x50x2	50x50x2	50x50x2	50x50x2
5000 mm	100x100x3	50x50x2	50x50x2	50x50x2	50x50x2
5500 mm	120x120x4	50x50x2	50x50x2	70x50x2	70x50x2
6000 mm	120x120x4	50x50x2	50x50x2	70x50x2	70x50x2
6500 mm	120x120x4	50x50x2	50x50x2	70x50x2	70x50x2
7000 mm	120x120x4	50x50x2	50x50x2	70x50x2	70x50x2
8000 mm	150x150x5	50x50x2	50x50x2	70x50x2	70x50x2
9000 mm	150x150x5	50x50x2	70x50x2	70x50x2	70x50x2
10.000 mm	160x160x5	50x50x2	70x50x3	70x50x3	70x50x3

\* Rights to change reserved

