



Detail 90° hinge

TECHNICAL DATA SIRA dp*

STABILITY:	Better thanks to square posts 60x60x2 mm
FENCE CONNECTION:	Standard (for request without the bar)
HINGES:	Adjustable, high quality 90°
LOCK:	Standard equipped with stainless steel LOCINOX lock plus eurocylinder with 3 keys included
LOCK CATCH:	Aluminium, provides solid locking
DROP BOLT:	1 Locinox drop bolt with aluminium Head Block + Keep (steel)
FRAME:	Made of square pipe 40x40x2 mm
GATE INFILL:	Double wire panel (8-6-8 50x200)
AVAILABLE FINISHES:	Hot dip galvanised according ISO EN 1461 Hot dip galvanised according ISO EN 1461 + powderpainted in any available RAL colour according NEN 5254

AVAILABLE MEASUREMENTS SIRA dp* (in mm)

ZINC & POWDER PAINT	
Widthe gate::	Available heights (in mm)
2000 mm	1030 1230 1430 1630 1830 2030
2250 mm**	1030 1230 1430 1630 1830 2030
2500 mm	1030 1230 1430 1630 1830 2030
2750 mm**	1030 1230 1430 1630 1830 2030
3000 mm	1030 1230 1430 1630 1830 2030

** 2250 mm 1 leaf 1000 mm + 1 leaf 1250 mm
2750 mm 1 leaf 1250 mm + 1 leaf 1500 mm

* Rights to change reserved

induline

induline[®]

PRIVAICON BV
HEKWERKEN

Privacon Hekwerken The Netherlands
MEULENVELDT 10 - 12 | 5451 HV MILL
Telephone: 0031 485 442 398
Fax: 0031 485 470 184
E-mail: info@privacon.nl