



Dura Ip

Above: detail 180° hinge
Under: SECURA keep

TECHNICAL DATA DURA Ip*

HINGES:	180° 4-dimensional adjustable (both left and right)
SECURITY STRIP (COMB):	Standard for gates from 1500 mm high
LOCK:	LOCINOX lock with stainless steel plus eurocylinder with 3 keys included
ANCHORING KEEP:	LOCINOX type SECURA
GATE INFILL:	Gate infill steel cage fence 50-200 mm (6 mm vertical wires and twin 8 mm horizontal wires fully welded at every intersection)
LEAFHEIGHT (WINGHEIGHT):	Minus 30 mm between the ground surface and the leaf
FENCE CONNECTION:	Optional for wire mesh or steel cage fence
AVAILABLE FINISHES:	Hot dip galvanised according ISO EN 1461 Hot dip galvanised according ISO EN 1461 + powderpainted in any available RAL colour according NEN 5254

ZINC & POWDER PAINT

Available heights: 830 mm | 1030 mm | 1230 mm | 1430 mm | 1630 mm | 1830 mm | 2030 mm | 2230 mm | 2430 mm

Width	Post section	Vert. pipe (lock)	Vert. pipe (hinge)	Upper crossbar	Lower crossbar
1000 mm	80x80x3	50x50x2	50x50x2	50x50x2	50x50x2
1250 mm	80x80x3	50x50x2	50x50x2	50x50x2	50x50x2
1500 mm	100x100x3	50x50x2	50x50x2	50x50x2	50x50x2
2000 mm	100x100x3	50x50x2	50x50x2	50x50x2	50x50x2
2500 mm	100x100x3	50x50x2	50x50x2	50x50x2	50x50x2
3000 mm	120x120x4	50x50x2	50x50x2	70x50x2	70x50x2
3500 mm	120x120x4	50x50x2	50x50x2	70x50x2	70x50x2
4000 mm	150x150x5	50x50x2	50x50x2	70x50x2	70x50x2
4500 mm	150x150x5	50x50x2	70x50x2	70x50x2	70x50x2
5000 mm	160x160x5	50x50x2	70x50x3	70x50x3	70x50x3

* Rights to change reserved