



Detail 90° hinge

TECHNICAL DATA KRISTA Ip*

STABILITY:	Better thanks to square posts
FENCE CONNECTION:	Standard (for request without the bar)
HINGES:	Adjustable, high quality 90°
LOCK:	Standard equipped with stainless steel LOCINOX lock plus eurocylinder with 3 keys included
LOCK CATCH:	Aluminium, provides solid locking
FRAME:	Made of square pipe 40x40x2 mm
GATE INFILL:	Double wire panel (8-6-8 50x200)
AVAILABLE FINISHES:	Hot dip galvanised according ISO EN 1461 Hot dip galvanised according ISO EN 1461 + powderpainted in any available RAL colour according NEN 5254

AVAILABLE MEASUREMENTS KRISTA Ip* (in mm)

ZINC & POWDER PAINT														
Width gate:	Post section:	Available heights (in mm)												
1000 mm	60x60x2	630	830	1030	1230	1430	1530	1630	1730	1830	1930	2030	2230	2430
1250 mm	60x60x2	630	830	1030	1230	1430	1530	1630	1730	1830	1930	2030	2230	2430
1500 mm	80x80x3	630	830	1030	1230	1430	1530	1630	1730	1830	1930	2030	2230	2430
1750 mm	80x80x3	630	830	1030	1230	1430	1530	1630	1730	1830	1930	2030	2230	2430
2000 mm	100x100x3	630	830	1030	1230	1430	1530	1630	1730	1830	1930	2030	2230	2430
2250 mm	100x100x3	630	830	1030	1230	1430	1530	1630	1730	1830	1930	2030	2230	2430
2500 mm	100x100x3	630	830	1030	1230	1430	1530	1630	1730	1830	1930	2030	2230	2430

* Rights to change reserved