

3D Profiled Wire Panels 5-5

Specifications:

Rigid Mesh Panel made of horizontal and vertical steel wires, welded together cross-wise
Rigidity is given by 100 mm high pressed beams
Panel length (width): 2505 mm
Panel height: see table
Wire diameter: 5 mm
Wire spacing horizontal: 50 mm
Wire spacing vertical: 200 mm (at profile beam: 50 mm)
Top Edge Projection: 30 mm



Available finishes:

- Self Colour (untreated)
- Hot Dipped Galvanised according to EN 1461
- Welded from pre-galvanised wire (Class D)*
- Welded from pre-galvanised wire (Class D) and Powder Coated in all available RAL colours

Panel Height (mm)	Self colour	Hot dipped galvanised	Welded from pre-galvanised wire	+ Powdercoated in RAL 6005
	Weight (Kg)	Weight (Kg)	Weight (Kg)	Weight (Kg)
830	8,7	9,8	9,5	9,7
1030	10,4	11,8	11,4	11,6
1230	12,2	13,8	13,3	13,6
1430	13,9	15,7	15,2	15,5
1530	15,4	17,4	16,8	17,2
1730	17,1	19,4	18,7	19,1
1930	18,9	21,3	20,6	21,0
2030	20,4	23,0	22,3	22,7
2330	22,3	25,2	24,4	24,9
2430	23,8	26,9	26,1	26,6

Supply of full pallets only. All finishes are packed per 50 pcs

* Guarantee on panels produced from pre-galvanised wire without further treatment can not be given.

Alternatives (available on request):

- Panels can be supplied in all available RAL colours

Lead time:

Within 6 weeks, subject to alterations