



## TECHNICAL DATA NIKA rsp\*

GATEPOSTS:	The guiding and slam portal are produced from a welded tube profile 80x80x3 mm and welded on a footplate.
GATE INFILL:	The slam portal is included a catch plate and a locker catcher. height 1500 - 2000 mm pipe 25 mm. Centre to centre distance 150 mm height 2500 mm pipe o 30 mm. Centre to centre distance 150 mm.
LOCK:	Locinox sliding gate lock in stainless steel.
WHEELS:	2 our 3 wheels with internal plate, half rounded u groof and bearing. The upper guide is also fitted with double plastic wheels with bearings.
TRACK:	Galvanised omega profile + runaway stop
AVAILABLE FINISHES:	Hot dip galvanised according ISO EN 1461 Hot dip galvanised according ISO EN 1461 + powderpainted in any available RAL colour according NEN 5254.

### ZINC & POWDER PAINT

Available heights: 800mm | 1000mm | 1250 mm | 1500 mm | 1800 mm | 2000 mm | 2500 mm

Free opening:	Lower crossbar	Vert. pipe	Vert. pipe left/right	Upper crossbar	No. of wheels
3000 mm	120x60x3	60x60x2	60x60x2	60x60x2	2
4000 mm	120x60x3	60x60x2	60x60x2	60x60x2	2
5000 mm	120x60x3	60x60x2	60x60x2	60x60x2	2
6000 mm	120x60x3	80x60x3	60x60x2	80x60x3	3
7000 mm	120x60x3	80x60x3	60x60x2	80x60x3	3
8000 mm	120x80x3	80x60x3	60x60x2	80x60x3	3
9000 mm	120x80x3	80x60x3	60x60x2	80x60x3	3
10000 mm	120x80x3	80x60x3	60x60x2	80x60x3	3

Free opening:	Total length panel (mm)	Free opening:	Total length panel (mm)
3000 mm	3650	6500 mm	7150
3500 mm	4150	7000 mm	7650
4000 mm	4650	7500 mm	8150
4500 mm	5150	8000 mm	8650
5000 mm	5650	8500 mm	9150
5500 mm	6150	9000 mm	9650
6000 mm	6650	9500 mm	10150
		10000 mm	10650



Secure and fast closing

\* Rights to change reserved

**induline**